Clean copy of Claims as amended

Should. (Twice Amended) A furniture piege, which comprises:

a plurality of rib units, each of which has (i) at least one functional surface such that a composite of each of the at least one functional surface of the plurality of rib units defines a functional surface of said furniture piece, and (ii) a single supporting member configured according to a pattern which varies from one rib unit to another such that a composite of the supporting members provides support for said furniture piece and its load wherein each rib has a front and a rear, and said support member in each rib emanates consistently among the rib units from either a front or rear portion thereof;

interconnecting means for securing each of the rib units to the others; and spacer means for situating each of the rib units in a position which, when secured by the interconnecting means, is separated from each of the adjoining rib units.

516C2-13. (Amended) A furniture piece comprising:

a plurality of interconnected rib units, each further comprising:

a first functional member defining a first functional surface for performing a first composite function for said furniture piece;

a supporting member emanating consistently from either a front or rear prtion of each rib unit;

wherein each supporting member of each rib unit is angularly displaced from its corresponding first functional member, independently of the remaining support members of

·b2

10

said plurality of rib units; and

wherein said plurality of rib units are interconnected such that the independently angled support members define a pattern such that the composite of the supporting members provides support for said furniture piece and its potential occupants.

(Amended) A furniture piece comprising:

a plurality of interconnected rib units, each comprising:

a functional surface such that a composite of the functional surface of each of said plurality of rib units defines a functional surface of said furniture piece; and

a supporting member emanating consistently from either a front or a rear portion of each rib unit; and

wherein each said supporting member is configured according to a pattern, with respect to adjacent supporting members, to define a composite supporting member which provides support for said furniture piece and its potential occupants.

h3